

## PU Tube



### ● Ordering Code

PU      08 60      B  
 |      |      |  
 PU;PU tube      Tube O.D.      Color

### Male Diameter of Hose

Serial Number	4	6	8	10	12
Caliber	φ 4	φ 6	φ 8	φ 10	φ 12

### ■ Character

1. With good resistance to high pressure, vibration, abrasion, climate, and fl action.
2. Light, easily fi xed, convenient for fi tting.
3. With high precision in dimension control, applying for all kinds of connector.
4. Many colors for choosing.

### ● Notice when fix the tube

1. Check is there any surface hurted or distortion to be ellipse.
2. The tube should touch the bottom of the fi tting when fi xed, or it may be leads to leak.
3. Make sure the tube can't be pushed out when fi xed up. (Never use excess strength, or it the fi tting will be destroyed)
4. when Releasing the tubes , please note :
5. Before releasing the tube, please ensure that the pressure to zero. press the releasing ring to the end uniformly, and pull out the tubes, if not completely push in the ring, the tubes could not be pulled out or damaged the tube, and tube scraps will remaind in inner tube, resulting in the possible of Leakage
6. while Assembly tube, the outer diameter of the tube shall meet the requirements of Tolerance;  
 PU specification 4,6,8 inthe range  $0.1\text{mm} - +0.1\text{mm}$  , and specifi cation 10,12 in the range  $-0.15\text{mm} - +0.15\text{mm}$

### ■ PU Tube/Standard Specification Sheet

Item	PU0320	PU0425	PU0640	PU0850	PU1065	PU1280	PU1611
O.D (mm)	φ 3.0	φ 4.0	φ 6.0	φ 8.0	φ 10.0	φ 12.0	φ 16.0
I.D (mm)	φ 2.0	φ 2.5	φ 4.0	φ 5	φ 6.5	φ 8.0	φ 11.0
W.P kgf/cm <sup>2</sup>	10	10	10	10	10	10	10

### ■ Tube color

