

UH Series High-Pressure Solenoid Valve



● UH-25




● UH-15



● UH-08

■ Graphics Sign



● Ordering Code

UH

Series

10

Pipe size
08; ZG1/4
10; ZG3/8
15; ZG1/2
20; ZG3/4
25; ZG1

AC220V

Standard Voltage
AC220V
AC110V
DC24V



■ Character

This guiding type valve adopts the diaphragm seal structure, with zero differential pressure starting function, large flow, simple structure, easy maintenance, good waterproof performance directions and multiple wiring directions.

■ Technical Parameter

Item \ Specification	UH-08	UH-10	UH-15	UH-20	UH-25
Material of Body	Cast copper				
Operating Method	Plunger Pilot				
Nominal Diameter(mm)	14	14	14	20	25
Applicable Medium	Air, Water, Oil(20CST Below)				
Pressure Range	0.3 ~ 5.0MPa				
Medium Temperature	0 ~ 90°C (No Freeze)				
Specified Voltage	AC24V、AC36V、AC110V、AC220V、DC24V、DC110V				
Operating Voltage Range	±10%				
Min. Activating Time	0.05S				
Install Method	Horizontal Installation				
Power	AC220V : 13VA 、 DC24V : 9W				

■ Figure Dimension



Specification	A	B	C	D
UH-08	65	33	90	16
UH-10	65	33	90	16
UH-15	65	33	90	16
UH-20	92	45	120	20
UH-25	92	45	120	20