

TL Series Lubricator



● TL2000-02



● TL4000-04

● Air Lubricator

It adopts balanced inlet with relief device. With the advantages of stable pressure, high precision, quick reaction and firm lockup, can be freely combined with other air-source treatment products.

● Ordering Code

TL

Series

2000

Type
1000
2000
3000
4000
5000

02

Pipe size
M5
01 : G1/8
02 : G1/4
03 : G3/8
04 : G1/2
06 : G3/4
10 : G1

U

Iron Shell
No Mark :
2000 No Iron Shell
3000 ~ 5000 With Iron Shell
U; 2000 With Iron Shell

■ Graphics Sign




■ Technical Parameter


Specification	TL1000-M5	TL2000-02/01	TL3000-03/02	TL4000-04/03	TL4000-06	TL5000-10/06
Applicable Medium	Air					
Rating Flow(L/min)	95	800	1700	5000	6300	7000
Work Pressure	0.05 ~ 0.85MPa					
Medium Temperature	0 ~ 60°C					
Recommended Lubricating Oil	ISOVG32 or Equivalent					
Min. Flow For Oil Drip	4L/min	15L/min	30L/min	50L/min	50L/min	190L/min
Lubricating Oil Capacity	4cm ³	25cm ³	50cm ³	130cm ³		

■ Figure Dimension


● TL1000-M5
TL2000-02/01



● TL3000-03/02 TL4000-04/03
TL4000-06



● TL5000-10/06



Type	A	B	C	D	E	F	G	H	I	J	M
TL1000-M5	25	87	14	27	28	6.5	M5	4.5	25	14	2
TL2000-02/01	40	131	34	40	19	6.5	G1/4	16	40	17	2.3
TL3000-03/02	53	146	30	53	40	8	G3/8	6.5	56	23	2.3
TL4000-04/03	70	180	37	70	54	10.5	G1/2	8.5	50	26	2.3
TL4000-06	76	199	37	70	54	10.5	G3/4	8.5	50	26	2.3
TL5000-10/06	90	254	46	90	66	13	G1	11	65	35	3.2

TL Series Lubricator (Metal Cup Type)



● TL2000-02M



● TL3000-03M

● Character

Metal cup is of metal material die-casting forming. It's reliable, durable ability and anti-explosion. Besides, it has long use life and safe use.

● Ordering Code

TL	2000	—	02	M
Series	Type		Pipe size	M: Metal cups
	2000		01 : G1/8	
	3000		02 : G1/4	
	4000		03 : G3/8	
	5000		04 : G1/2	
			06 : G3/4	
			10 : G1	

■ Graphics Sign




■ Technical Parameter


Specification	TL2000-02M/01M	TL3000-03M/02M	TL4000-04M/03M	TL4000-06M	TL5000-10M/06M
Applicable Medium	Air				
Rating Flow(L/min)	800	1700	5000	6300	7000
Work Pressure	0.05 ~ 0.85MPa				
Medium Temperature	0 ~ 60°C				
Recommended Lubricating Oil	ISOVG32 or Equivalent				
Min. Flow For Oil Drip	15L/min	30L/min	50L/min	50L/min	190L/min
Lubricating Oil Capacity	25cm ³	50cm ³	130cm ³		

■ Figure Dimension


● TL2000-02M/01M



● TL3000-03M/02M TL4000-04M/03M TL4000-06M



● TL5000-10M/06M



Type	A	B	C	D	E	F	G	H	I	J	M
TL2000-02M/01M	40	131	34	40	19	6.5	G1/4	16	40	17	2.3
TL3000-03M/02M	53	146	30	53	40	8	G3/8	6.5	56	23	2.3
TL4000-04M/03M	70	180	37	70	54	10.5	G1/2	8.5	50	26	2.3
TL4000-06M	76	199	37	70	54	10.5	G3/4	8.5	50	26	2.3
TL5000-10M/06M	90	254	46	90	66	13	G1	11	65	35	3.2